

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
5 January 2006 (05.01.2006)

PCT

(10) International Publication Number
WO 2006/001534 A2

(51) International Patent Classification⁷: G03F 7/095

[JP/JP]; c/o CANON KABUSHIKI KAISHA, 3-30-2, Shimomaruko, Ohta-ku, Tokyo 1468501 (JP). OKANO, Akihiko [JP/JP]; c/o CANON KABUSHIKI KAISHA, 3-30-2, Shimomaruko, Ohta-ku, Tokyo 1468501 (JP).

(21) International Application Number:
PCT/JP2005/012270

(22) International Filing Date: 27 June 2005 (27.06.2005)

(74) Agents: OKABE, Masao et al.; No. 602, Fuji Bldg., 2-3, Marunouchi 3-chome, Chiyoda-ku, Tokyo 1000005 (JP).

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2004-190481 28 June 2004 (28.06.2004) JP

(71) Applicant (for all designated States except US): CANON KABUSHIKI KAISHA [JP/JP]; 3-30-2, Shimomaruko, Ohta-ku, Tokyo 1468501 (JP).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG, KM, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(72) Inventors; and

(75) Inventors/Applicants (for US only): KUBOTA, Masahiko [JP/JP]; c/o CANON KABUSHIKI KAISHA, 3-30-2, Shimomaruko, Ohta-ku, Tokyo 1468501 (JP). SUZUKI, Takumi [JP/JP]; c/o CANON KABUSHIKI KAISHA, 3-30-2, Shimomaruko, Ohta-ku, Tokyo 1468501 (JP). SATO, Tamaki [JP/JP]; c/o CANON KABUSHIKI KAISHA, 3-30-2, Shimomaruko, Ohta-ku, Tokyo 1468501 (JP). KANRI, Ryoji [JP/JP]; c/o CANON KABUSHIKI KAISHA, 3-30-2, Shimomaruko, Ohta-ku, Tokyo 1468501 (JP). HATTA, Maki [JP/JP]; c/o CANON KABUSHIKI KAISHA, 3-30-2, Shimomaruko, Ohta-ku, Tokyo 1468501 (JP). ASAI, Kazuhiro [JP/JP]; c/o CANON KABUSHIKI KAISHA, 3-30-2, Shimomaruko, Ohta-ku, Tokyo 1468501 (JP). SHIBA, Shoji [JP/JP]; c/o CANON KABUSHIKI KAISHA, 3-30-2, Shimomaruko, Ohta-ku, Tokyo 1468501 (JP). ISHIKURA, Hiroe


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— without international search report and to be republished upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: METHOD FOR MANUFACTURING MINUTE STRUCTURE, METHOD FOR MANUFACTURING LIQUID DISCHARGE HEAD, AND LIQUID DISCHARGE HEAD



ing a desired pattern in the above-mentioned second positive type photosensitive material layer as the upper layer by decomposing reaction without decomposing reaction of the above-mentioned first positive type photosensitive material layer, development using a developing solution, and then, a step of forming a desired pattern in the above-mentioned first positive type photosensitive material layer as the lower layer by decomposing reaction of a predetermined area, and development, whereby a pattern of a convex shape is manufactured in the substrate by executing the above-mentioned steps.

(57) Abstract: A method for manufacturing a minute structure comprises a step of forming a first ionizing radiation decomposing type positive type resist layer to be sensitized by an ionizing radiation of a first wavelength range, a step of forming a second ionizing radiation decomposing type positive type resist layer to be sensitized by an ionizing radiation of a second wavelength range on the first positive type photosensitive material layer, a step of forming

DESCRIPTION

METHOD FOR MANUFACTURING MINUTE STRUCTURE, METHOD FOR
MANUFACTURING LIQUID DISCHARGE HEAD, AND LIQUID
DISCHARGE HEAD

5 TECHNICAL FIELD

The present invention relates to a method for manufacturing a minute structure using a photosensitive resin, and a liquid discharge head for generating recording liquid small droplets used for
10 the ink jet recording system and a method for manufacturing the head. In particular, the present invention relates to a method for manufacturing a head comprising an ink liquid flow path shape, capable of stably discharging minute liquid droplets
15 enabling a high image quality, and furthermore capable of realizing a high speed recording operation. Furthermore, the present invention relates to an ink jet head with the ink discharge properties improved, based on the above-mentioned method for manufacturing
20 an ink jet head.

BACKGROUND ART

A liquid discharge head applied for the ink jet recording system (liquid discharge recording system)
25 for recording by discharging a recording liquid such as an ink in general comprises a liquid flow path, a liquid discharge energy generating part provided in a